

Printing date 06.02.2019 Version number 7 Revision: 06.02.2019

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: 187666 A7691 EVVA MULTISPRAY -200 ml-
- · Article number: T7001132, 74 2546
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture:

Cleaning agent/ Cleaner

Lubricant

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: IGS Aerosols GmbH

I II . . 1

Im Hemmet 1

79664 WEHR/BADEN

**GERMANY** 

productsafety@igsaerosols.com

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number: During normal opening times: +49 7762 800-734

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

GHS07

CHSU0

Printing date 06.02.2019 Version number 7 Revision: 06.02.2019

Trade name: 187666 A7691 EVVA MULTISPRAY -200 ml-

(Contd. of page 1)

- · Signal word Danger
- · Hazard-determining components of labelling:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

*P211* Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

· Additional information:

EUH208 Contains Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts. May produce an allergic reaction.

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
EC number: 921-024-6 Reg.nr.: 01-2119475514-35-xxxx	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n- hexane ♦ Flam. Liq. 2, H225; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ↑ Skin Irrit. 2, H315; STOT SE 3, H336	30-50%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane  The property of the pr	20-30%
EC number: 927-241-2 Reg.nr.: 01-2119471843-32	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics  ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336; Aquatic Chronic 3, H412	10-20%
CAS: 8042-47-5 EINECS: 232-455-8 Reg.nr.: 01-2119487078-27	Mineral oil  Asp. Tox. 1, H304	10-20%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1, H220	<i>≥</i> 1-<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	isobutane Flam. Gas 1, H220; Press. Gas C, H280	<i>≥</i> 1-<10%

(Contd. on page 3)

Printing date 06.02.2019 Version number 7 Revision: 06.02.2019

Trade name: 187666 A7691 EVVA MULTISPRAY -200 ml-

(Contd. of page 2)

· Regulation (EC) No 648/2004 on detergents / Labelling for contents	
aliphatic hydrocarbons	≥30%
amphoteric surfactants	<5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.
- · Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

#### **SECTION 6: Accidental release measures**

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

 $\cdot \textit{ 6.2 Environmental precautions:} \\$ 

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

 $\cdot$  6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 4)

Printing date 06.02.2019 Version number 7 Revision: 06.02.2019

Trade name: 187666 A7691 EVVA MULTISPRAY -200 ml-

(Contd. of page 3)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

Short term filter device:

type A

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Not necessary if room is well-ventilated.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.4$  mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

*Value for the permeation:* Level  $\leq 6$ 

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Printing date 06.02.2019 Version number 7 Revision: 06.02.2019

Trade name: 187666 A7691 EVVA MULTISPRAY -200 ml-

(Contd. of page 4)

· Eye protection: Not required.

### **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:
Colour:
Clight yellow
Characteristic
Odour threshold:
Not determined.

PH-value:
Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Not applicable, as aerosol.

· Flash point:  $-60 \, ^{\circ}C$ 

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 287 °C

· Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Explosion limits:

 Lower:
 0.8 Vol %

 Upper:
 10.9 Vol %

· Vapour pressure at 20 °C: 3,200 hPa

Density at 20 °C: 0.66 g/cm³
 Relative density Not determined.
 Vapour density Not determined.
 Evaporation rate Not applicable.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

**Dynamic:** Not determined. **Kinematic:** Not determined.

· Solvent content:

 Organic solvents:
 86.6 %

 VOC (EC)
 86.58 %

• 9.2 Other information No further relevant information available.

### **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.

(Contd. on page 6)

Printing date 06.02.2019 Version number 7 Revision: 06.02.2019

Trade name: 187666 A7691 EVVA MULTISPRAY -200 ml-

(Contd. of page 5)

- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:					
Hydrocarb	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane					
Oral	LD50	>5,840 mg/kg (rat) (OECD 401)				
Dermal	LD50	>2,920 mg/kg (rabbit) (OECD 402)				
Inhalative	LC50/4 h	25.2 mg/l (rat)				
Hydrocarb	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics					
Oral	LD50	>5,000 mg/kg (rat)				
Dermal	LD50	>5,000 mg/kg (rabbit)				

- Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity:

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

EL50/48h 3 mg/l (Daphnia magna (Großer Wasserfloh))

EL50/72h 30 mg/l ((Alge (Pseudokirchneriella subcapitata)))

LL50/96h 11.4 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 7)

Printing date 06.02.2019 Version number 7 Revision: 06.02.2019

Trade name: 187666 A7691 EVVA MULTISPRAY -200 ml-

(Contd. of page 6)

· 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

15 01 10\* packaging containing residues of or contaminated by hazardous substances

15 01 04 metallic packaging

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport infor	
· 14.1 UN-Number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name · ADR · IMDG · IATA	1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS AEROSOLS (Hydrocarbons, C6-C7, n-alkanes, isoalkane cyclics, < 5% n-hexane, 2-ethylhexanoic acid, compour with dodecylamine (1:1)), MARINE POLLUTANT AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
· ADR	
Class	2 5F Gases.
· Label 	2.1
· IMDG	
· Class	2.1
· Label	2.1
IATA	
· Class	2.1
· Label	2.1
· 14.4 Packing group · ADR, IMDG, IATA	Void

Printing date 06.02.2019 Version number 7 Revision: 06.02.2019

Trade name: 187666 A7691 EVVA MULTISPRAY -200 ml-

	(Contd. of page
14.5 Environmental hazards:	Product contains environmentally hazardous substance Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, 5% n-hexane
Marine pollutant:	Yes Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user Danger code (Kemler):	Warning: Gases.
EMS Number:	F- $D$ , $S$ - $U$
Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litr Category A. For AEROSOLS with a capacity above 1 litr Category B. For WASTE AEROSOLS: Category C, Cle of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litr Segregation as for class 9. Stow "separated from" class except for division 1.4. For AEROSOLS with a capaci above 1 litre: Segregation as for the appropria subdivision of class 2. For WASTE AEROSOL Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to Ann	ex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
UN ''Model Regulation'':	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALI HAZARDOUS

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Printing date 06.02.2019 Version number 7 Revision: 06.02.2019

Trade name: 187666 A7691 EVVA MULTISPRAY -200 ml-

(Contd. of page 8)

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

#### · Department issuing SDS: Product safety department

· Contact: Mr. Weber, PhD.

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas C: Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

 $A quatic\ Chronic\ 3:\ Hazardous\ to\ the\ aquatic\ environment\ -\ long\ -term\ aquatic\ hazard\ -\ Category\ 3$ 

\* Data compared to the previous version altered.

EU